

## No. 3695RB Hose Barb Check Valve



Used for food and beverage, biodiesel, hydraulic and pneumatic applications, or where resistance is needed for aggressive fuels and chemicals. Also where excellent heat stability is required. Rated for temperatures up to 350°F. Not for steam use.

SKU: 3695RB-H



Type: Check Valve / Material: 316 Stainless / Seal: Viton / Fluid Types: Chemicals, Drinking Water, Food and Beverage, Fuels, Hydraulic Fluid, Non-Potable Water / Special Use: Hose Barb Ends

### 316 Stainless Steel Check Valve with Viton Rubber Poppet and Hose Barb Ends

The No. 3695RB Fusion™ check valve is made from solid 316 stainless steel bar, with all internal components also of 316 stainless steel. Designed to operate in any position, a sensitive spring has been added to close the poppet automatically. The Viton rubber poppet is fully-formed around a solid steel insert to provide greater strength in commercial applications. The patented Fusion™ valve design offers flexibility in configuring the end connections, with selections from pipe threads to hydraulic connections to hose barbs. All valves are 100% American-Made and built to last. Contact Strataflo now to see how this product can be customized for your application.

Part Number	Pipe Size	Flow Rate (Cv)	Overall Length	Valve Diameter	Valve Weight
3695RB-H25	1/4"	0.3 GPM	4.23"	1.12"	0.45 lb.
3695RB-H38	3/8"	0.9 GPM	4.23"	1.12"	0.45 lb.
3695RB-H50	1/2"	2.4 GPM	4.37"	1.12"	0.50 lb.
3695RB-H75	3/4"	6.5 GPM	4.61"	1.24"	0.55 lb.
3695RB-H100	1"	9.9 GPM	4.77"	1.49"	0.95 lb.

Cv is flow (GPM) with a 1 psi differential pressure. Products listed contain NPT end connections. Contact Strataflo for technical specifications if another style of end connection is desired.

# Materials & Operational Specifications

Part Name	Specs
Body	316 Stainless Steel
Stem	316 Stainless Steel
Poppet	Viton Rubber
Spring	316 Stainless Steel
Spring Retainer	316 Stainless Steel
Country of Origin	Made in the USA
Max. Temperature	350°F
Working Pressure	300 psi
Cracking Pressure	1-2 lbs.
Opt. Cracking Pressure	1/2, 5, or 10 lbs.

2010 Lakeview Dr.  
Fort Wayne, IN 46808  
260-482-4366  
sales@strataflo.com