

No. F200 Foot Valve



Application: Used as an all purpose foot valve for multiple applications, including cold water, ethylene, and glycol.

SKU: F200



Type: Foot Valve / Material: Lead-Free Bronze / Seal: Buna-S / Fluid Type: Drinking Water / Special Use: NSF Certified

Lead-Free Foot Valve with Buna-S Rubber Poppet

The No. F200 is certified by NSF to contain less than 0.25% lead by weighted average and is compliant with CA, LA, MD, VT state laws and U.S. Safe Water Drinking Act. They are manufactured from a one-piece cast brass body. The unique strainer consists of a helically wound stainless steel spring wire which is durable and cannot corrode. The No. 200 comes standard with a Buna-S rubber poppet, an extremely durable compound for use with potable drinking water. Each valve is tested twice for casting integrity and backflow prevention. All valves are 100% American-made and built to last.

Dimensions

Part Number	Pipe Size	Flow Rate (Cv)	Overall Length	Valve Diameter	Valve Weight
F200-075	3/4"	8 GPM	3.63"	1.31"	0.40 lb.
F200-100	1"	16 GPM	4.27"	1.78"	0.75 lb.
F200-125	1-1/4"	27 GPM	4.74"	2.28"	1.15 lb.
F200A-125	1-1/4" *	14 GPM	4.00"	1.89"	0.75 lb.
F200-150	1-1/2"	32 GPM	5.64"	2.56"	1.50 lb.
F200-200	2"	64 GPM	5.41"	3.25"	2.90 lb.
F200-250	2-1/2"	83 GPM	6.36"	3.88"	4.75 lb.
F200-300	3" M *	83 GPM	6.36"	3.88"	4.65 lb.

Cv is flow (GPM) with a 1 psi differential pressure. NPT threaded. *No. F200A-Special 1-1/4" valve will enter a 2" pipe for cold water service. ** 3" Male NPT thread.

Materials & Operational Specifications

Part Name	Specs
Body	Cast Bronze C89833
Stem	303 Stainless Steel
Poppet	Buna-S Rubber
Strainer Coil	302 Stainless Steel
Nipple	Delrin
Locknut	18/8 Stainless Steel
Country of Origin	Made in the USA
Max. Temperature	225°F
Working Pressure	400 psi

2010 Lakeview Dr.
Fort Wayne, IN 46808
260-482-4366
sales@strataflo.com